



Technical drawing of a beam (Binnen) with dimensions and a cross-section. The beam is shown in perspective, with a cross-section at the top left. The cross-section is a trapezoid with a top width of 40 mm and a bottom width of 40 mm, and a height of 4.0 mm. The beam is labeled "Binnen" and has a length of 1.5 m. The beam is supported by a base with a width of 1.5 m. The beam is shown in a perspective view, with a cross-section at the top left. The cross-section is a trapezoid with a top width of 40 mm and a bottom width of 40 mm, and a height of 4.0 mm. The beam is labeled "Binnen" and has a length of 1.5 m. The beam is supported by a base with a width of 1.5 m.

BUVA rationale bouwproducten Postbus 262 2990 AG Barendrecht Tel: +31 (0) 180 697500 Fax: +31 (0) 180 697507	FT	BUVA Activ-Pilot Stand. <u>Stolpraam</u> <u>beslag draai deel</u> met vaste krukhoogte			
	Controlle	Deze tekening is met de grootste zorg samengesteld. BUVA, <i>rationele bouwproducten</i> , aanvaardt nochans geen verantwoordelijkheid voor enige schade, voortvloeiend uit onjuistheden of anderszins onvolkomenheden in de inhoud van deze tekening.			
	Vrijgifte	Uitvoering	Verdect beslag SELECT	Documentnummer	Revisie
				201007.POS/3.08S	A 02
				Type	Blaad
				1/1	Formaat
					A-3